

Non-Reversing, Three Pole Special Purpose Contactors With AC Coil (Open type only) ❶

Full Load Amps	Locked Rotor Amps - 3Ø			Resistive Amps ❸	Maximum Horsepower						Auxiliary Contacts per Contactor		Catalog Number	Price
					1 Ø		3 Ø							
	200V/230V	460V	575V		115V	230V	200V/208V	230V	460V	575V	NO	NC		
15	91	91	66	25	1-1/2	3	4	5	10	10	1	0	CNX-205-*	171.02
											0	1	CNX-206-*	171.02
30	180	150	120	40	2	5	7-1/2	10	20	20	1	0	CNX-207-*	243.58
											0	1	CNX-208-*	243.58
40	240	200	160	50	3	5	10	10	25	25	0	0	CNX-209-00-*	282.97
											1	0	CNX-209-10-*	302.66
											0	1	CNX-209-01-*	302.66
50	300	250	200	65	3	7-1/2	10	15	30	30	0	0	CNX-212-00-*	316.14
											1	0	CNX-212-10-*	336.87
											0	1	CNX-212-01-*	336.87
90	540	450	360	120	~	~	25	30	60	60	0	0	CNX-218-00-*	498.56
											1	0	CNX-218-10-*	518.26
											0	1	CNX-218-01-*	518.26



CNX-208-120
 Special Purpose contactor

Description

Series CNX Special Purpose Contactors are standard CA7 contactors that have been tested, approved and labeled by UL for heating, ventilation and air conditioning (HVAC) applications. ❷

Coil Codes ❷

AC Coil Code	Voltage Range	
	50 Hz	60 Hz
24Z	24V	24V
120	110V	120V
208	~	208V
220W	~	208V-240V
240	220V	277V
277	240V	440V
380	380V-400V	480V
480	440V	480V
600	550V	600V

Ordering Instructions

Specify Catalog Number	
Replace (*) with Coil Code	See Coil Codes on this page.

- ❶ All CNX contactors listed here are ARI (Air Conditioning and Refrigeration Institute) approved.
- ❷ Other voltages available, see page A56.
- ❸ Reference page A77 for Operation Life Data.