

Accessories for KT9

Accessory	Description	Color	For Use With	Catalog Number
KT9-KRY	Lockable Twist Knob For 1 padlock 46 mm (3/16 in.) diameter shackle Can be locked in OFF position	Black	KT_9-32S, KT_9-40H, KTU9	КТ9-КМ
			KT_7-45H	KT7-KN1
		Red/Yellow	KT_9-32S, KT_9-40H, KTU9	KT9-KRY
KT9-KN			KT_7-45H	KT7-KRY1
кт9-мз	Locking Tag • Padlock attachment to the lockable handles • Up to three padlocks 48 mm (5/16 in.) dia. shackle	Red	KT9-KN KT9-KRY1	КТ9-М3
			KT7-KN1 KT7-KRY1	KT7-DS
300***	Terminal Adapter for Type E Applications • Required for self-protected combination motor controller (Type E) application of KT_9-32S, KT_9-40H and KT_7-45H • Not for use with bus bars		KT_9-32S, KT_9-40H	КТ9-40-ТЕ
			KT_7-45H	KT7-45-TE
	Anti-Tamper Shield • Provides protection against inadvertent adjusment of		KT_9-32S, KT_9-40H	KT9-CA
4 P	 Sold only in packages of 10. Order 10 pieces to receive 1 pkg. of 10 		KT_7-45H	KT7-25-CA
1 11 2 12 5 13	Screw Adaptor • For screw fixing of motor protection circuit breaker • Sold only in packages of 10. Order 10 pieces to receive 1 pkg. of 10		KT_9-32S, KT_9-40H, KTU9	KT9-N45
			KT_7-45H	KT7-45-AS

Marking Systems

Component	Description	Pkg. Qty.	Catalog Number
132	Label Sheet - 1 sheet with 105 self-adhesive paper labels each, 6 x17mm	1	CA7-FMS



- $oldsymbol{0}$ Terminal Adaptors are supplied as standard on enclosed KT9 and CX7 starters, as well as, CLE- assembled products, assuring they can be used in Type E applications. Alternatively, compact busbar supply block KT9-_-A2E or -A3E meet Type E requirements for terminal spacing.

 Minimum quantity is one package of 100.