

Series KT9

Connecting Modules (for connecting KTA7, KTB7 or KTC7 into KT_9 to CA8, CA7 AC coil, or CA7 Electronic DC coil contactors) @

Module	Туре	Description	For Connecting	Catalog Number O
**	ECO Connection Module 12A (IEC) , 11A (UL)	 For DOL and revering starters Eco-starters mount on single DIN Rail (KT_9 on DIN Rail) Electrical and mechanical interconnection of KT_9 and CA8 contractors 	KT_9-32S to CA8	KT9-32S-PEK12
	ECO Connection Module 25A (IEC) , 22A (UL)	 Eco-starters mount on single DIN Rail (KT_9 on DIN Rail) Electrical and mechanical interconnection of KT_9 MPCB and CA7 (with AC coils or 24V DC electronic coils) contactors 	KT_9-32S to CA7-923	KT9-32S-PEC23
			KT_9-40H to CA7-923	KT9-40H-PEC23
	ECO Connection Module 38A (IEC) , 34A (UL)	 Eco-starters mount on single DIN Rail (KT_9 on DIN Rail) Electrical and mechanical interconnection of KT_9 MPCB and CA9 (with AC coils or 24V DC electronic coils) contactors 	KT_9 -40H to CA7-3037	KT9-40H-PEC37
XXX	ECO Connection Module <u>KT9PNC23</u> 25A (IEC), 24A (UL) <u>KT9PNC37</u> 38A (IEC), 34A (UL)	 Contactor and MPCB MUST BE mounted separately on (2) DIN Rails Electrical interconnection of KT 9 and CA7 	KT_9-32S to CA7-923	KT9-32S-PNC23
			KT_9-40H to CA7-923	KT9-40H-PNC23
			KT_9-40H to CA7-3037	KT9-40H-PNC37
	Connecting Modules — 25 and 45 A	 Contactor and MPCB MUST BE mounted separately on (2) DIN Rails Electrical Interconnection of KT_7-45H and CA7 (with AC coils) 	KT_7-45H to CA7-3037	KT7-45H-PNC37
			KT_7-45H to CA7-43	KT7-45H-PNC43

Coil Modules

\sim	Coil Extension Modules	Provides access to coil terminals on 3-component starters	CA7-923	KT9-32S-PSC23
			CA7-3055	KT9-80H-PSC43
n n 7			CA7-3055	KT7-45H-PSC43

Type W Mounting Modules

Module	Description	Width (mm)	Catalog Number
	Rottom rail is movable for easy assembly and disassembly	45	W-32489
		54	W-32490
	Long Mounting Module - See Section D for Connecting Modules • Provides support for KT7 + PCS Softstarter, CA7 + PCS Softstarter or KTB7 + CA7+CEP7 • Top rail is specifically designed for KT7 • Bottom rail is movable for easy assembly and disassembly • Complete unit mounts to two 35mm DIN-rails or one 70mm DIN-rail or screw mounts • 283 mm long	45	W-32496
		54	W-32497
Silver Law State	Spacer for Mounting Module - Fits between 45mm and 54mm for Reversing applications (228 mm long)	9	W-32955
	Dovetail Joints - Used to connect two mounting medules together (Sold in packages of 50)		W-32954

• cURus Approved (File # E33916).

Not for use with KTU9 Circuit Breakers