

CX7 Non-Reversing Controller Modifications

Pilot Device Options - required		
Select one option only ①②③	Replace ▼ in catalog number with	Price Adder
START-STOP Multi-function	3U	Standard
I-O Multi-function	4U	Standard
OFF-ON 2-Position Selector switch	6	Standard
HAND-OFF-AUTO 3-Position Selector switch	7	Standard
Run Pilot Light Green	1G	Standard
Run Pilot Light Red	1R	Standard
Overload Alarm Pilot Light	1Y	Standard
D7-N8 22mm Hole Plug	0	Standard
Additional KT7 Auxiliaries & Trip Contacts		Change "-A10" to...
Front Mount 300V maximum		
1 NO + 1 NC Auxiliary	-A11	63.36
2 NO Auxiliaries	-A20	63.36
1 NO SC+OL + 1 NC Auxiliary	-T10A01	80.74
1 NO SC+OL + 1 NO Auxiliary	-T10A10	80.74

CX7 Non-Reversing Controller Additions

Addition	Add to end of catalog number	Price Adder
CA7 Contactor Accessories		
Electronic Interface ④	-JE	96.07
Surge Suppressor RC	-C	55.19
Surge Suppressor Varistor	-V	55.19
CA7 Auxiliary Contacts ⑤⑥		
1 NO Auxiliary	-S10 ⓧ	45.99
1 NC Auxiliary	-S01 ⓧ	45.99
1 NO + 1 NC Auxiliary	-S11	58.25
2 NO Auxiliaries	-S20	58.25
2 NC Auxiliaries	-S02	58.25
Alternate Aux. Contact Arrangement (CA7 only)		
1 NC in lieu of standard 1 NO	-SX10	17.37
2 NC in lieu of standard 2 NO (on CXU7 only)	-SX2	17.37
Unwired Terminal Blocks Specify quantity (▼)	-▼TB	22.48

CXU7 Reversing Controller Modifications

Pilot Device Options - required		
Select one option only ①②③	Replace ▼ in catalog number with	Price Adder
FOR-STOP-REV Multi-function	3U	Standard
UP-STOP-DOWN Multi-function	4U	Standard
OPEN-STOP-CLOSE Multi-function	5U	Standard
FOR-STOP-REV 3-Position Selector switch	6	Standard
UP-OFF-DOWN 3-Position Selector switch	7	Standard
OPEN-OFF-CLOSE 3-Position Selector switch	8	Standard
Overload Alarm Pilot Light	1Y	Standard
D7-N8 22mm Hole Plug	0	Standard
Additional KT7 Auxiliaries & Trip Contacts		Change "-A10" to...
Front Mount 300V maximum		
1 NO + 1 NC Auxiliary	-A11	63.36
2 NO Auxiliaries	-A20	63.36
1 NO SC+OL + 1 NC Auxiliary	-T10A01	80.74
1 NO SC+OL + 1 NO Auxiliary	-T10A10	80.74

CXU7 Reversing Controller Additions

Addition	Add to end of catalog number	Price Adder
CA7 Contactor Accessories		
Electronic Interface ④	-JE	192.14
Surge Suppressor RC	-C	110.38
Surge Suppressor Varistor	-V	110.38

- ① KS7-C0C4R only has (1) 22mm hole to accommodate (1) pilot device.
- ② Currently supply D7 multi-function pushbuttons as standard which do not require protective boots to meet Type 4X.
See Section H in this catalog for description (all suffix's ending in "U").
- ③ Pilot Lights may be applied with 24VAC/VDC, 120VAC or 240VAC Control Circuit. Pilot Lights with 380 VAC...575VAC require a control circuit transformer.

- ④ CRI7E-24 will be used. CRI7E-12 by special order only.
- ⑤ See page A47 for limitations on adding auxiliaries to Electronic DC Coil contactors.
- ⑥ Additional auxiliaries are per contactor. Number of auxiliaries is double for reversing applications. Multiply price adder by two (2).

F
Enclosed Motor Circuit Controllers