














Auer Signal

Modular Beacons M 160 mm ø











cULus Type 4/4X/13 CE

Type	Description	Specifications	Catalog Number	Price	Catalog Number	Price
	Replace  with lens color		Horizontal Base Mounting 		Pole Base Mounting  M20 1/2" NPT	
 MLL (Shown with bracket)	MLL Steady Beacon  (Halogen bulb included)	24 V AC/DC 110/120 V AC 230/240 V AC	819 102 405 819 102 310 819 102 313	297.80	 819 310 405 819 310 310 819 310 313 <i>(No Clear 230V)</i>	360.84
	MBL Flashing Beacon  (Halogen bulb included)	24 V AC/DC 110/120 V AC 230/240 V AC	839 100 405 839 100 310 839 100 313 <i>(Amber or red only)</i>	386.48	 839 310 405 839 310 310 839 310 313 <i>(No Red 120V)</i>	449.52
	MFL Strobe Beacon (Xenon tube included)	24 V AC/DC 110/120 V AC 230/240 V AC	849 100 405 849 100 310 849 100 313 <i>(Amber, Red, Blue, Yellow only)</i>	591.48	 849 310 405 849 310 310 849 310 313 <i>(No Amber, Red 120V, No Clear 24V)</i>	654.52
	MRL Rotating Mirror Beacon  Halogen bulb included Not available in Clear, Green or Blue	24 V AC/DC 110/120 V AC 230/240 V AC	419 100 405 419 100 310 419 100 313	378.19 424.99 424.99	419 300 405 419 300 310 419 300 313	419 310 405 419 310 310 419 310 313
			Catalog Number	Price		
	Bracket		819 200 900	37.11		
	Mounting plate for UL type 4, 4X, 13		819 202 900	20.63		
	Magnetic mount		819 203 900	108.85		






Modular Beacons M 120 mm ø

cULus Type 4/4X/13 CE

Type	Description	Specifications	Catalog Number	Price	Catalog Number	Price
	Replace  with lens color		Horizontal Base Mounting 		Pole Base Mounting  M20 1/2" NPT	
 MLM	MLM Steady Beacon  (Halogen bulb included)	24 V AC/DC 110/120 V AC 230/240 V AC	818 102 405 818 102 310 818 102 313	199.46	 818 310 405 818 310 310 818 310 313	238.26
	MBM Flashing Beacon  (Halogen bulb included)	24 V AC/DC 110/120 V AC 230/240 V AC	838 100 405 838 100 310 838 100 313 <i>(Only Amber and Red)</i>	275.66	 838 310 405 838 310 310 838 310 313 <i>(No Amber, Red, Green 24V)</i>	314.44
	MFM Strobe Beacon (Xenon tube included)	24 V AC/DC 110/120 V AC 230/240 V AC	848 100 405 848 100 310 848 100 313 <i>(No Amber 120V)</i>	405.86	 848 310 405 848 310 310 848 310 313 <i>(Only Green, Yellow 24V, No Amber 120V)</i>	444.66
	MRM Rotating Mirror Beacon  Halogen bulb included Not available in Clear, Green or Blue	24 V AC/DC 110/120 V AC 230/240 V AC	418 100 405 418 100 310 418 100 313	346.32 393.12 393.12	418 300 405 418 300 310 418 300 313	418 310 405 418 310 310 418 310 313
			Catalog Number	Price		
	Bracket		818 200 900	32.44		
	Mounting plate for UL type 4, 4X, 13		818 202 900	17.41		
	Magnetic mount		818 203 900	98.97		



Pole Mounts also available for 120mm beacons. See next page.





-  To complete the catalog no., replace the  with one of the following numbers for desired lens color: **1** = Amber, **2** = Red, **4** = Clear, **5** = Blue, **6** = Green, **7** = Yellow.
-  Halogen bulb included. For replacement bulbs see page J39.




Auer Signal





Modular Beacons M 90 mm ø

UL[®] Type 4/4X/13 CE

Type	Description	Specifications	Catalog Number	Price	Catalog Number		Price
	Replace ☉ with lens color		Horizontal Base Mounting ①		Pole Base Mounting ① M20 1/2" NPT		
	MLS Steady Beacon ② (Halogen bulb included)	24 V AC/DC 110/120 V AC 230/240 V AC	817 102 405 817 102 310 817 102 313	153.75		817 31☉ 405 817 31☉ 310 817 31☉ 313 <i>(No Blue 120V)</i>	173.12
	MBS Flashing Beacon ② (Halogen bulb included)	24 V AC/DC 110/120 V AC 230/240 V AC	837 102 405 837 102 310 837 102 313	216.10		837 31☉ 405 837 31☉ 310 837 31☉ 313 <i>(No Red 24V, No Red, Blue, Yellow 120V)</i>	235.47
	MFS Strobe Beacon (Xenon tube included)	24 V AC/DC 110/120 V AC 230/240 V AC	847 10☉ 405 847 10☉ 310 847 10☉ 313	360.15		847 31☉ 405 847 31☉ 310 847 31☉ 313 <i>(No Amber Red 24V, No Amber 120V, No Blue 240V)</i>	379.53
	MRS Rotating Mirror Beacon ② Halogen bulb included Not available in Clear, Green or Blue	24 V AC/DC 110/120 V AC 230/240 V AC	417 10☉ 405 417 10☉ 310 417 10☉ 313	281.20 316.93 316.93	417 30☉ 405 417 30☉ 310 417 30☉ 313	417 31☉ 405 417 31☉ 310 417 31☉ 313	300.57 336.30 336.30
			Catalog Number	Price			
Bracket			817 200 900	26.85			
Mounting plate for UL type 4, 4X, 13			817 202 900	16.17			
Magnetic mount			817 203 900	80.97			



Modular Beacon M Accessories

Type	Description	Catalog Number	Price
	Bonding kit for conduit installations	819 201 900	16.17
	AKV Cable gland M20 x 1.5	698 800 026	8.90
	MMR ③ Pole Mount Aluminum tube with plastic foot	5 cm	698 806 007 53.98
		10 cm	698 806 008 62.97
		25 cm	698 806 009 71.98
		40 cm	698 806 010 80.97
	MSR ③ Pole Mount Stainless steel tube with zinc die cast foot, powder coated, black	5 cm	698 806 021 67.47
		10 cm	698 806 022 76.47
		25 cm	698 806 023 89.97
		40 cm	698 806 024 107.96

① To complete the catalog no., replace the ☉ with one of the following numbers for desired lens color:

1 = Amber, 2 = Red, 4 = Clear, 5 = Blue, 6 = Green, 7 = Yellow.

② Halogen bulb included. For replacement bulbs see page J39.

③ For use with Modular Beacons M 120mm, 90mm and Beacons N only