







Mini Horn-Signal Beacons

CE

Type	Description	Specifications	Catalog Number	Price
	Replace ② with lens color		Grey Housing ①	
	KLL Mini Horn Signal Beacon with cone Steady of Flashing (no bulb) ② ③ 92 dB @ VDC 88 dB @ VAC, 50 Hz	24 V DC 24 V AC, 50 Hz 48 V AC, 50 Hz 230 V AC, 50 Hz	710 11① 005 710 11① 105 710 11① 108 710 11① 113	155.88
	KLF Mini Horn Strobe Beacon with cone Xenon tube included ③ 92 dB @ VDC 88 dB @ VAC, 50 Hz	24 V DC 230/240 V AC, 50 Hz	710 12① 005 710 12① 113	236.04
	KDL Mini Horn Signal Beacon without cone Steady of Flashing (no bulb) ② ③ 92 dB @ VDC 88 dB @ VAC, 50 Hz	24 V DC 24 V AC, 50 Hz 48 V AC, 50 Hz 230 V AC, 50 Hz	710 01① 005 710 01① 105 710 01① 108 710 01① 113	160.56
	KDF Mini Horn Strobe Beacon without cone Xenon tube included ③ 92 dB @ VDC 88 dB @ VAC, 50 Hz	24 V DC 230/240 V AC, 50 Hz	710 02① 005 710 02① 113	238.54

Mini Horns

CE

Type	Description	Specifications	Catalog Number	Price
			Grey Housing	
	KLH Mini Horn with cone continuous tone 92 dB @ VDC 88 dB @ VAC, 50 Hz	12 V DC 24 V DC 110 V DC 220 V DC 24 V AC, 50 Hz 48 V AC, 50 Hz 230 V AC, 50 Hz	710 100 004 710 100 005 710 100 010 710 100 013 710 100 105 710 100 108 710 100 113	82.58
	KDH Mini Horn without cone continuous tone 92 dB @ VDC 88 dB @ VAC, 50 Hz	12 V DC 24 V DC 220 V DC 24 V AC, 50 Hz 48 V AC, 50 Hz 230 V AC, 50 Hz	710 000 004 710 000 005 710 000 013 710 000 105 710 000 108 710 000 113	75.23

① To complete the catalog no., replace the ① with one of the following numbers for desired lens color:

1 = Amber, 2 = Red, 7 = Yellow.

② Bulb not included. Order separately on page J39.

③ Other voltages and colors available by special order only. Contact factor for more information.

Non-UL Signaling